

## LED Highbay 3030 Series

- ☑ Proprietary Lens design to reduce glare and increase beam density.
- ☑ Powder coated lamp cover to suit industrial use and style.
- ☑ Patented driver design for prolonged work life.
- ☑ Patented day light sensor and motion sensor function.



Model NO.	Rated Power	Lumen Output	Rated Voltage	Frequency	PF	CCT	CRI	Beam Angle	Ambient Temperature	Number Of Lamps
BA-S-50	50W	6000Lm	200-240Vac	50/60Hz	>0.9	2700-6500K	>80	60° / 90°	-20~45C	1
BA-S-70	70W	8400Lm	200-240Vac	50/60Hz	>0.9	2700-6500K	>80	60° / 90°	-20~45C	1
BA-S-80	80W	9600Lm	200-240Vac	50/60Hz	>0.9	2700-6500K	>80	60° / 90°	-20~45C	1
BA-S-90	90W	10800Lm	200-240Vac	50/60Hz	>0.9	2700-6500K	>80	60° / 90°	-20~45C	1
BA-S-100	100W	12000Lm	200-240Vac	50/60Hz	>0.9	2700-6500K	>80	60° / 90°	-20~45C	1
BA-S-110	110W	13200Lm	200-240Vac	50/60Hz	>0.9	2700-6500K	>80	60° / 90°	-20~45C	1
BA-S-120	120W	14400Lm	200-240Vac	50/60Hz	>0.9	2700-6500K	>80	60° / 90°	-20~45C	1
BA-S-150	150W	18000Lm	200-240Vac	50/60Hz	>0.9	2700-6500K	>80	60° / 90°	-20~45C	1
BA-S-175	175W	21000Lm	200-240Vac	50/60Hz	>0.9	2700-6500K	>80	60° / 90°	-20~45C	1
BA-S-200	200W	24000Lm	200-240Vac	50/60Hz	>0.9	2700-6500K	>80	60° / 90°	-20~45C	1